



DOCSIS 3.0 8x4 Cable Modem

Model 5345



The Zoom Model 5345 cable modem meets the cable industry's DOCSIS 3.0 standard for speeds up to 343 Mbps, and also works with lower-speed DOCSIS 2.0 and 1.1 services. Full-Band Capture Digital Tuning allows service providers to offer more channels and accelerate downloads. The Model 5345 has been tested and certified by CableLabs® to work with nearly all U.S. cable services.

This modem can be plugged into any Windows, Mac, or Linux computer with an Ethernet port. The Model 5345 can also be plugged into routers and routers with wireless capability for sharing of your high-speed service with multiple devices. With its easy installation, high speed, and broad compatibility, the Model 5345 is the perfect choice for almost any cable modem user.

Features of the Model 5345 include:

■ Easy installation

■ Fast data speed

Up to 343 Mbps downstream and 123 Mbps upstream with bonding of up to eight channels downstream and four channels upstream

Full-Band Capture Digital Tuning lets service providers deliver faster, more reliable Internet.

■ Fast 10/100/1000 Base-T Ethernet connectivity

To support the very fast DOCSIS 3.0 data transfers and provide compatibility and easy installation with almost any Windows, Mac or Linux computer, as well as both wired and wireless routers

■ Supports IPv4 and IPv6

Support for the latest Internet addressing keeps your equipment current

■ Five status-reporting LEDs

LAN, Online, Upstream, Downstream, and Power lights allow easy status monitoring.

■ DOCSIS 3.0 compatible, and compatible with earlier standards

Provides support for the latest data-over-cable standard DOCSIS 3.0, as well as DOCSIS 1.1 and 2.0, to ensure operation with the fastest available services and compatibility with all U.S. operators.

DOCSIS (Data Over Cable Service Interface Specification) is the industry standard for transmission of Internet data over cable-based systems in the U.S. and many other countries. Check with your service provider to ensure they use the DOCSIS standard.

■ Extensive SNMP management support

Includes MIB-II, Ethernet-Like MIB, Bridge MIB, Cable Device MIB, Baseline Privacy Interface MIB, RF Interface MIB

■ Compact, space-saving design

■ Experienced, U.S.-based technical support for both consumers and service providers

■ Certified by CableLabs®

■ Two year warranty and U.S. support from Zoom Telephonics, a leader in communications products since 1977

Specifications

General

Cable modem service interface:	F-type female 75 Ω (standard coaxial connector)
Ethernet LAN interface:	RJ-45 10/100/1000 Mbps Ethernet, with Auto-MDI/MDIX
Status indicators:	Ethernet link, Connection Status, Upstream link, Downstream link, Power
Size:	5.7 x 4.1 x 1.6 inches (14.4 x 10.5 x 4 cm)
Power adapter:	Level V energy-saving, switching power supply with 12 Volt DC, 1 Amp output. NEMA 5-15 (North American style) plug is standard. Other plugs are available.
Operating temperature:	32° to 104° F (0° to 40° C)
System requirements:	<ul style="list-style-type: none"> - The cable modem must be connected to a cable modem service that uses any of the DOCSIS standards – 3.0, 2.0, 1.1 - An available Ethernet port on a Windows, Mac, or Linux computer, or an available WAN Ethernet port on a wired or wireless router.
Approvals:	FCC part 15B, Bureau Veritas for IEC 60950-1:2005 (2nd Ed.) safety, CE, CableLabs®
Warranty:	Two years
Package contents:	Cable modem, power cube, Ethernet cable, Quick Start flyer

Operating Parameters

Downstream:	
Data rate*:	Up to 343 Mbps (8 channels), Up to 43 Mbps (single channel)
Frequency:	88 to 1002 MHz (edge to edge)
Modulation:	64 or 256 QAM
Operating level range:	-15 to +15 dBmV
Upstream:	
Data rate*:	Up to 123 Mbps (4 channels), Up to 31 Mbps (single channel)
Frequency:	5 to 42 MHz (edge to edge)
Modulation:	QPSK, 8QAM, 16QAM, 32QAM, 64QAM, 128QAM, 256QAM
Operating level range:	A-TDMA: +8 to +54 dBmV (32QAM, 64QAM) +8 to +58 dBmV (QPSK) S-CDMA: +8 to +53 dBmV (all modulations)
Security:	DOCSIS 3.0 Security (BPI+, EAE, SSD)
Networking:	
Network protocols:	IPv4, IPv6, TCP, UDP, ARP, ICMP, DHCP, FTP, TFTP, SNMP, HTTP
Application protocol:	SNMP v1/v2/v3
DHCP client:	Automatically retrieves IP and DNS server address from DHCP server at ISP
ToD (RFC68):	ToD support for local and MSO time synchronization
TFTP client:	TFTP support for cable modem configuration file download
Management:	Web-based management interface utility
Core chipset:	Broadcom BCM3383D

* Data throughput will be reduced by network overhead. Delivered data speeds are also dependent upon the configuration and capacity of the data-over-cable service on which the 5345 is used.



Cable Modem Back Panel



International Headquarters
Zoom Telephonics, Inc
207 South Street
Boston, MA, 02111
USA
Tel: 617-535-9383
Fax: 617-423-3923

Email: sales@zoomtel.com

Website: www.zoomtel.com

OTCQB: ZMTP

© 2015 Zoom Telephonics, Inc. 207 South Street, Boston, MA 02111
Zoom is a registered trademark of Zoom Telephonics, Inc.
All other registered trademarks and trademarks used herein are the property of their respective holders.